Product: K18 Industrial Use Only (Not Human Use)

MSDS ID: H1256

Revised Date: 01/01/19

Replaces Date: 10/20/17

1. Product and Company Identification

Product Code: K18 (XX) where XX is the percentage of K18 in the solution

Trade Name(s): K18

Product Type: A solution of Quaternary Ammonium Silane-Functionalized Methacrylate Resin in

Ethanol

Recommended Use: Antimicrobial material Restrictions: None identified

Company: DM Healthcare Products, Inc.

10080 Willow Creek Rd. San Diego, CA 92131

Telephone: 858-348-1122

Emergency phone number (spill, leak, fire, exposure or accident):

US Domestic (800) 535-5053 (INFOTRAC) Includes Canada and Mexico

International +1 (352) 323-3500 China Specific (86) 400-120-0761 Germany Specific (49) 0800-181-2924 Australia Specific (61) 1-300-366-961

2. Hazards Identification

EMERGENCY OVERVIEW:

GHS Classification:

Physical Hazards

Flammable liquid Category 2 (H225)

Health Hazards

Acute Toxicity (Oral)

Skin Corrosion /Irritation

Category 4 (H302)

Category 2 (H315)

Skin Sensitization

Category 1 (H317)

Specific Target Organ Toxicity (Single Exposure) Category 3 (H335) Respiratory

System

ENVIRONMENTAL HAZARDS

Hazardous to the Aquatic Environment (Acute)

Not Classified
Hazardous to the Aquatic Environment (Chronic)

Not Classified

PICTOGRAM



SIGNAL WORD Danger

HAZARD STATEMENT(S)

H225 Flammable liquid and vapor

H302 Harmful if swallowed.

Date printed: 5/7/2019 Page 1 of 7

Product: K18 Industrial Use Only (Not Human Use)

MSDS ID: H1256

Revised Date: 01/01/19

Replaces Date: 10/20/17

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation

PRECAUTIONARY STATEMENT(S)

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

P312 Call a POISON CENTER or doctor/ physician if you feel unwell.

P321 Specific treatment (see supplemental first aid instructions on this label).

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

HMIS Classification:

Health Hazard: 2* Flammability: 3 Physical Hazards: 0

NFPA Rating:

Health Hazard: 2*
Fire: 3
Reactivity Hazard: 0

3. Composition Information

SUBSTANCE / MIXTURE MIXTURE

GENERIC NAME K18 Antimicrobial material in ethanol.

INGREDIENT	CAS No:	Classification	Concentration
K18 Antimicrobial Material	1566577-95-4	Ac tox. 4	10 – 50 %
Ethanol	64-17-5	Flam. Liq. 2; Skin irrit. 2; Skin Sens.1; STOT SE 3	50 – 90 %

Date printed: 5/7/2019 Page 2 of 7

Product: K18 Industrial Use Only (Not Human Use)

Revised Date: 01/01/19 MSDS ID: H1256 Replaces Date: 10/20/17

First Aid Measures

GENERAL ADVICE:

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous

INHALATION

Remove the victim to fresh air. If not breathing, give artificial respiration. Consult a physician.

SKIN CONTACT

Remove all contaminated clothing, shoes and socks from the affected areas as quickly as possible. Wash the affected area under tepid running water using a mild soap.

EYE CONTACT

Gently rinse the affected eyes with clean water for at least 15 minutes. Arrange for transport to the nearest medical facility for examination and treatment by a physician as soon as possible.

INGESTION

Do not induce vomiting. Do not give an unconscious person anything to drink. Get medical attention.

5. Fire and Explosion Hazard Data

SPECIFIC HAZARDS WITH REGARD TO FIRE-EXTINGUISHING MEASURES

Shut off the supply. Use extinguishing equipment from the up-wind side. If necessary wear protective clothing including a breathing apparatus.

If the fire extends to the surrounding area, cool the facilities by spraying with water. Immediately move containers to safe place if possible.

EXTINGUISHING MEDIA

In case of fire use water spray, alcohol-resistant foam, dry chemical powder, carbon dioxide, dry sand.

SPECIAL HAZARDS ARISING FROM THE MIXTURE

No data available.

6. Accidental Release Measures

CAUTIONS FOR PERSONNEL

Wear proper equipment and avoid contact with skin and inhalation of vapor. Keep personnel away from downwind of any fire. Shut off all sources of ignition.

CAUTIONS FOR ENVIRONMENT

Prevent spills from entering waterways.

REMOVAL MEASURE

Shut off the leakage source to stop the leakage. For small spill, absorb spill with absorbent and collect in chemical waste container. For large spill, prevent contamination of surrounding area and move material to a safe place for collection.

PREVENTION OF SECOND ACCIDENT

Remove nearby sources of ignition and prepare extinguishing media.

Date printed: 5/7/2019 Page 3 of 7

Product: K18 Industrial Use Only (Not Human Use)

Revised Date: 01/01/19

MSDS ID: H1256 Replaces Date: 10/20/17

7. Handling and Storage

HANDLING

Engineering measures

Avoid contact with skin and eyes. Wear proper protective equipment to prevent contact with skin or inhalation of the vapor. Pay attention to fire – keep away from sources of ignition. No Smoking.

Cautions for safety handling

Use with an enclosed system or a local exhaust ventilation.

STORAGE

Adequate storage condition

Keep container tightly closed and in a dry and well-ventilated place. Avoid direct rays from the sun. No fire.

Safety adequate container materials

Glass, steel, stainless

8. Exposure Controls and Personal Protection Measures

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

Components	CAS-No.	Value	Control paramete	Basis	
Ethanol	64-17-5	TWA	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)	
Remarks	Upper Respiratory Tract Irritation. Confirmed animal carcinogen with unknown relevance to humans				
		TWA	1,000 ppm 1,900 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000	
		TWA	1,000 ppm 1,900 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
	The value in mg/m3 is approximate.				
		TWA	1,000 ppm 1,900 mg/m3	USA. NIOSH Recommended Exposure Limits	

ENGINEERING MEASURES

Use only with adequate ventilation and in closed systems.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION

If necessary, wear a full-face respirator with multipurpose combination cartridges as a backup to engineering controls.

EYE PROTECTION

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU)

SKIN AND BODY PROTECTION

Handle with gloves. Use protective clothing of flame retardant and antistatic materials, protective boots.

Date printed: 5/7/2019 Page 4 of 7

Product: K18 Industrial Use Only (Not Human Use)

Revised Date: 01/01/19

MSDS ID: H1256 Replaces Date: 10/20/17

9. Physical / Chemical Characteristics

APPEARLANCE, PHYSICAL STATE, COLOR, ODOR

Liquid, Colorless, Characteristic Alcohol Odor

SAFETY DATA

Boiling point 78°C (172°F) <Ethanol>
Melting point -114°C (-173°F) <Ethanol>
Flash Point 14°C (57°F) <Ethanol>

Explosion Limit Upper: 19 vol%, Lower: 3.3 vol% < Ethanol>

Vapor Pressure 59.5 hPa (20°C) < Ethanol>

10. Reactivity Hazard Data

STABILITY Stable under recommended storage conditions.

CONDITIONS TO AVOID May polymerize on exposure to light. Heat flames and sparks. Extremes

of temperature and direct sunlight.

REACTIVITY No data available.

INCOMPATIBILITY Oxidizing agents, alkali metals, peroxides, bases, acids, reducing

agents, halogens.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide (under fire conditions).

11. Toxicological Information

Acute Toxicity (Oral) LD50I – rat – 7,060 mg/kg <Ethanol>

Acute Toxicity (Dermal) No data available

Acute Toxicity (Inhalation) LC50 - rat - 10 h - 20,000 mg/m³ < Ethanol>

Acute Toxicity (Dusts and Mists)
Skin Corrosion /Irritation
Serious Eye Damage /Eye Irritation
Respiratory or Skin Sensitization
Carcinogenicity

No data available
No data available
No data available
Mouse – Oral

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver:Tumors. Blood:Lymphomas

including Hodgkin's disease.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified

as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified

as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified

as a carcinogen or potential carcinogen by OSHA.

Reproductive Toxicity Human – female – Oral <Ethanol>

Effects on Newborn: Apgar score (human only). Drug

dependence <Ethanol>

Specific Target Organ Toxicity (Single Exposure) May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure)

Aspiration Hazard

No data available

No data available

12. Ecological Information

Hazardous to the Aquatic Environment (Acute)

Not Classified
Hazardous to the Aquatic Environment (Chronic)

Not Classified

Date printed: 5/7/2019 Page 5 of 7

Product: K18 Industrial Use Only (Not Human Use)

MSDS ID: H1256

Revised Date: 01/01/19

Replaces Date: 10/20/17

13. Disposal Considerations

This material may be burned in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable.. Follow all regulations in your country.

14. Transport Information

DOT (US)

UN Class 3 (Flammable liquid)

UN number 1993

UN proper shipping name Ethanol
Packing group II

Reportable Quantity (RQ) - Marine pollutant No

IATA

UN Class 3 (Flammable liquid)

UN number 1993

UN proper shipping name Ethanol
Packing group II

Sub risk -

Follow all regulations in your country.

15. Regulatory Information

TSCA Status:

One component of this material is not listed nor exempt from listing on the TSCA inventory. For R&D use only by trained professionals

OSHA Hazards

Flammable liquid, Target Organ Effect, Carcinogen

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Ethanol CAS-No. 64-17-5

Pennsylvania Right To Know Components

Ethanol CAS-No. 64-17-5

New Jersey Right To Know Components

Ethanol CAS-No. 64-17-5

Date printed: 5/7/2019 Page 6 of 7

Product: K18 Industrial Use Only (Not Human Use)

MSDS ID: H1256

Revised Date: 01/01/19

Replaces Date: 10/20/17

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. Other Information

The opinions expressed herein are those of qualified experts within DM Healthcare Products, Inc. We believe that the information contained herein is current, as of the date of this MSDS. Because the use of this information and of these opinions, and the conditions of use of this product, are not within the control of DM Healthcare Products, Inc., it is the user's legal obligation to determine the conditions of safe use of this product.

Date printed: 5/7/2019 Page 7 of 7